

SV-22

Total No. of Pages : 3

Seat No.	
-------------	--

T.E. (Civil Engineering) (Part-III) (Semester - VI) (New)**Examination, May - 2018****GEOTECHNICAL ENGINEERING - II****Sub. Code : 66874****Day and Date : Saturday, 05 - 05 - 2018****Total Marks : 100****Time : 2.30 p.m. to 5.30 p.m.**

- Instructions :
- 1) All questions are compulsory.
 - 2) Figures to the right indicate full marks.
 - 3) Use of non-programmable calculator.
 - 4) Assume suitable data wherever necessary and state it clearly.

SECTION-I

Q1) a) Explain necessity of site exploration and give the criteria for deciding depth and number of bore holes. [8]

b) Explain Wash boring with a neat sketch. [8]

OR

b) Explain modes of failures of rock with examples. [8]

Q2) a) The following data was obtained from a plate load test carried out on a 60 cm square plate at a depth of 2 m below GL on a sandy soil which extends upto large depth. Determine the settlement of foundation 3.0m×3.0 m carrying a load of 110 t and located at a depth of 2 m from GL. [9]

Load (t/m ²)	5	10	15	20	25	30	35	40
Settlement (mm)	2.0	4.0	7.5	11.0	16.3	23.5	34.0	45.0

b) Explain standard penetration test. [9]

OR

b) Write IS code method equation for calculating bearing capacity. Explain each term involved in it. Also explain how eccentricity of loading is considered. [9]

P.T.O.

SV-22
[8]

Q3) a) Write notes on (Any two):

- i) Calculation of consolidation settlement.
- ii) Floating foundation.
- iii) Minimum depth of footing.
- iv) Tilt and angular distortion.

b) A combined trapezoidal footing has two columns 0.5×0.5 m each carrying loads of 2000 kN and 1500 kN. The c/c spacing of columns is of 6.0 m. Heavy column is on property line. Calculate dimensions of the combined trapezoidal footing by taking allowable soil pressure as 200 kN/m^2 . **[8]**

SECTION-II

Q4) a) A group of 16 piles is arranged in square pattern with pile diameter as 45 cm and c/c distance of piles as 1.5 m. The soil has cohesion of 50 kN/m^2 . Length of each pile is 10 m. Neglecting end bearing and taking adhesion factor as 0.7, **[9]**

- i) Calculate group efficiency
- ii) Mention whether the group would fail by individual or by block action

b) Explain pile load test with sketch. **[9]**

OR

b) Explain under reamed piles and its construction. **[9]**

Q5) a) Explain with neat sketch, different shapes of well foundation and its suitability. **[8]**

b) Write short note on: (Any two) **[8]**

- i) Common types of cofferdams
- ii) Pneumatic caissons
- iii) Remedial measures for tilt and shift
- iv) Soil pressure distribution for sheet pile wall

SV-22

Q6) a) Discuss vibrofloation technique for ground improvement in detail. [8]

- b) Data from method of slices for a slope of soil with $c = 4 \text{ t/m}^2$, $\phi = 25^\circ$ and $\gamma = 19 \text{ t/m}^3$ is given below. Determine factor of safety. Take angle subtended at centre of curvature by arc of failure as 104° and radius of curvature $R = 10 \text{ m}$. [8]

Slice no.	1	2	3	4	5	6	7	8
Area (m^2)	0.55	3.0	4.65	5.8	6.15	6.35	3.3	0.2
α (degree)	-24	-12	-1	11	23	36	52	68

OR

- b) A 7 m deep slope of 1:1 is to be made in a cohesive soil. The soil has a cohesion of 25 kN/m^2 , the angle of friction is 25° and bulk unit weight is 18 kN/m^3 . [8]

i) Find factor of safety w.r.t. cohesion

ii) What will be critical height of slope?

Take $S_n = 0.083$ for 1:1 slope and $\phi = 45^\circ$.

